



# Cable Parameters

## Cable Description

Description	Part Number	Size (mm <sup>2</sup> )	L/R Ratio (μH/Ω)	Inductance (μH/m)	Capacitance (pF/m)
Sensing head cable (Trolex) 2 x 4mm + 2 x 1.5mm	CAC2P2FNP	4	50	0.8	410
SILBUS cable 5 pair 5 pairs x 1.5mm individual screened	CAC5P5FNP	1.5	28	0.9	78
SILBUS cable single pair 2 x 1.5mm	CAC2CONNPI	1.5	28	0.9	78
Pulline Cable for SILBUS Long distance conveyors 5 core 3 x 1.5mm + 1 x 2mm + 1 x 1mm	CAC5CIBYU	1.5 2 1	Various	Various	Various

## Cable Parameters

Description	Part Number	Size (mm <sup>2</sup> )	L/R Ratio (μH/Ω)	Inductance (μH/m)	Capacitance (pF/m)
½" Hose and Cable 2.5mm <sup>2</sup>	8P001	2.5	43	1	52
BM3 Cable 6 Core 0.5mm <sup>2</sup>	BM3015	0.5	15	1.1	107
Cable 5 Core 2.5mm <sup>2</sup>	CABL25	2.5	45	0.9	100
Pullwire 6 Core 0.75mm <sup>2</sup>	CON05/B	0.75	25	1.2	50
SILBUS Cable 2 Core 1.5mm <sup>2</sup>	SIL078	1.5	28	0.9	78
Cable 4mm <sup>2</sup> + 2 Pair 1mm <sup>2</sup>	G2000	4	60	0.9	104.5
Cable 10mm <sup>2</sup> + Twin Pair 0.75mm <sup>2</sup>	G2000A	10	123	0.8	130
Cable 4mm <sup>2</sup> + Twin Pair 1mm <sup>2</sup>	G2000B	4	60	0.9	213

Cables, Plugs and Sockets

AUSTDAC PTY. LTD.

ABN: 31 002 654 695