



Types

Industrial Relays

Midi Industrial Relays

RCP 8 (2 Poles)

RCP 11 (3 Poles)

RMI 2-10 (2 Poles)

RMI 4-5 (4 Poles)



Dimensions (mm) H x W x D
No. of Contacts
Contact rating
Features standard with:

56 x 35.5 x 35.5
2 Change-over (octal)
10 A
Test button/Flag/LED

56 x 35.5 x 35.5
3 change-over (undecal)
10 A
Test button/Flag/LED

36 x 21.5 x 28
2 Change-over
10 A
Test button/Flag/LED

36 x 21.5 x 28
4 Change-over
5 A
Test button/Flag/LED

Output Specifications

Max. load AC1
Min. load
Electrical life
Switching power

12 A / 250 VAC
100 mA / 12 VDC
> 100.000 cycles
2500 VA (resistive)

12 A / 250 VAC
100 mA / 125 VDC
> 100.000 cycles
2500 VA (resistive)

12 A / 250 VAC
100 mA / 5 VDC
> 100.000 cycles
2500 VA (resistive)

6 A / 250 VAC
100 mA / 5 VDC
> 100.000 cycles
1250 VA (resistive)

General Specifications

Voltage ranges VDC
Voltage ranges VAC
Insulation according to Consumption
Approvals/Conformity

6 - 12 - 24 - 48 - 60 100 - 110
6 - 12 - 24 - 48 115/120 - 230
EN 61810-5
1.5 W DC-2.5 VA AC
UL-CSA-TUV-IMQ

6 - 12 - 24 - 48 - 60 100 - 110
6 - 12 - 24 - 48 115/120 - 230
EN 61810-5
1.5 W DC-2.5 VA AC
UL-CSA-TUV-IMQ

5 - 6 - 12 - 24 - 48 60 - 110
6 - 12 - 24 - 48 115/120 - 230
EN 61810-5
1 W DC-1.5 VA AC
UL-CSA-TUV-IMQ

5 - 6 - 12 - 24 - 48 60 - 110
6 - 12 - 24 - 48 115/120 - 230
EN 61810-5
1 W DC-1.5 VA AC
UL-CSA-TUV-IMQ

References

5 VDC
6 VDC
6 VAC
12 VAC
12 VDC
24 VAC
24 VDC
48 VAC
48 VDC
60 VDC
100 VDC
110 VDC
115/120 VAC
230 VAC

RCP80026DC
RCP80026AC
RCP800212AC
RCP800212DC
RCP800224AC
RCP800224DC
RCP800248AC
RCP800248DC
RCP800260DC
RCP8002100DC
RCP8002110DC
RCP8002115/120AC
RCP8002230DC

RCP110036DC
RCP110036AC
RCP1100312AC
RCP1100312DC
RCP1100324AC
RCP1100324DC
RCP1100348AC
RCP1100348DC
RCP1100360DC
RCP11003100DC
RCP11003110DC
RCP11003115/120AC
RCP11003230DC


RMIA/B2-105DC
RMIA/B2-106AC
RMIA/B2-106DC
RMIA/B2-1012AC
RMIA/B2-1012DC
RMIA/B2-1024AC
RMIA/B2-1024DC
RMIA/B2-1048AC
RMIA/B2-1048DC
RMIA/B2-1060DC
RMIA/B2-10110DC
RMIA/B2-10115AC
RMIA/B2-10230AC

RMIA/B4-55DC
RMIA/B4-56AC
RMIA/B4-56AC
RMIA/B4-512AC
RMIA/B4-512DC
RMIA/B4-524AC
RMIA/B4-524DC
RMIA/B4-548AC
RMIA/B4-548DC
RMIA/B4-560DC
RMIA/B4-5110DC
RMIA/B4-5115AC
RMIA/B4-5230AC

Types

ZPD 8 / ZPD 11

ZMI 15/2N - ZMI 15/4N



General Specifications

Dimensions (mm) H x W x D
Rated volt. / Rated curr.
Insulation voltage
Socket material
Mounting
Protection degree
Approvals

65 X 27 X 38
400 VAC / 10 A
> 3 kV
Self-ext. PA6 + GF (V1)
DIN-rail
IP 20
CE,UL,CSA (10A 300VCA)

Octal and Undecal socket
Unintentional touch protection.
Standardized markings.

42.5 x 75 x 27
300 VAC / 12 A
> 4 kV
Self-ext. PA6 + GF (V2)
DIN-rail
IP 20
CE,UL,CSA

14 pole socket. Plug-in terminal connection.
Unintentional touch protection. Screw with captive wire clamp for 2 wire 2.5 mm ² .
Standardized markings.

References

For RCP 8 / RCP 11 Relay
For RMI 2-10 / RMI 4-5 Relay

ZPD 8
ZPD 11

ZMI 15/2N
ZMI 15/4N

Switch